

IN THE CLAIMS:

Amend Claims 1-17 as follows and add Claims 18-20:

1. (Currently amended) Hydraulic system, comprising at least one hydraulic drive means (1), a conduit system (10) connected to the hydraulic drive means for ~~convey~~ conveying hydraulic liquid to and from the hydraulic drive means, where the conduit system comprises a conduit circuit (11) containing hydraulic liquid, connected to the hydraulic drive means, a pump (12) for generating a flow of hydraulic fluid in the conduit system and a motor (13) to power the pump, ~~characterized in that,~~ wherein

[-] the pump (12) is arranged to control the flow of hydraulic liquid in said circuit (11),
and

~~that~~ the hydraulic drive means (1) is controllable substantially only by controlling the flow of hydraulic liquid in said circuit (11) by means of the pump (12).

2. (Currently amended) Hydraulic system according to claim 1, ~~characterized in that,~~ wherein the pump (12) is arranged to control direction of the flow of hydraulic liquid in said circuit (11) and thereby control the direction of action of the hydraulic drive means (1).

3. (Currently amended) Hydraulic system according to claim 1 ~~or 2,~~ characterized in that, wherein the pump (12) is arranged to control the flow rate of the hydraulic liquid in said circuit (11) and thereby control the effective rate of the hydraulic drive means (1).

4. (Currently amended) Hydraulic system according to claim 1 ~~any of claims 1-3,~~
~~characterized in that,~~ wherein the motor (13), that powers the pump (12), is arranged to
control the pump to control the flow of hydraulic liquid in said circuit (11).

5. (Currently amended) Hydraulic system according to claim 1 ~~any preceding~~
~~claims, characterized in that~~ wherein said motor (13) is an electrically driven motor.

6. (Currently amended) Hydraulic system according to claim 1 ~~any preceding~~
~~claims, characterized in that,~~ wherein it comprises means for regenerating mechanical
energy transmitted to the hydraulic drive means (1), due to loading of the hydraulic drive
means.

7. (Currently amended) Hydraulic system according to claim 6, ~~characterized in~~
~~that,~~ wherein said energy regeneration means include the motor (13), that is arranged to
be driven as a generator by the pump (12), for regeneration of energy when said
mechanical energy transmitted to the hydraulic drive means (1) is transformed to liquid
energy of the hydraulic liquid in said circuit (11) and thereby powers the pump (12).

8. (Currently amended) Hydraulic system according to claim 6 ~~or 7,~~ ~~characterized~~
~~in that,~~ wherein it comprises means to store regenerated energy.

9. (Currently amended) Hydraulic system according to claim 8, ~~characterized in~~
~~that,~~ wherein said energy storage means comprises at least one rechargeable battery.

10. (Currently amended) Hydraulic system according to claim 6 ~~any of claims 6-9,~~
~~characterized in that,~~ wherein the motor (13) is powered by the energy regenerated by said
energy regenerated means.

11. (Currently amended) Hydraulic system according to claim 10, ~~characterized in~~
~~that,~~ wherein the motor (13) is powered by regenerated energy stored in said energy
storage means.

12. (Currently amended) Hydraulic system according to claim 1 ~~any of the~~
~~preceding claims, characterized in that,~~ wherein the hydraulic drive means (1) is a
hydraulic cylinder.

13. (Currently amended) Hydraulic system according to claim 12, ~~characterized in~~
~~that,~~ wherein the hydraulic cylinder has chambers (4, 5) containing hydraulic liquid,
arranged on opposite sides of a piston (2), with a piston rod (3) connected to the piston
received in one chamber (5), and ~~that~~ the system comprises an arrangement (16-22)
arranged to provide a supply of hydraulic liquid to said conduit circuit (11) on controlling the
hydraulic cylinder (1) to move the piston in a direction for reducing the volume of said one
chamber (5) and to tap hydraulic liquid from the conduit circuit (11) on movement of the
piston in the opposite direction.

14. (Currently amended) Hydraulic system according to claim 13, ~~characterized in that,~~ wherein the arrangement comprises at least two conduits connected to a tank (19) for hydraulic liquid and to the conduit circuit (11) via a valve (17, 18) each.

15. (Currently amended) Hydraulic system according to claim 14, ~~characterized in that,~~ wherein a first of the conduits connected to the hydraulic liquid tank has a one-way valve (18) that only makes the flow of hydraulic liquid from the tank (19) to the conduit circuit (11) possible to supply hydraulic liquid to the conduit circuit on movement of the piston in the direction for reducing the volume in said one chamber (5) when the valve (17) is closed in the second conduit (21) to the tank, whereby the second conduit is connected to the conduit circuit (11) nearer to said one chamber (5) than to the first conduit (22).

16. (Currently amended) Hydraulic system according to claim 15, ~~characterized in that,~~ wherein the valve (17) in the second conduit (21) is controllable to be open when the piston is displaced in the direction for reducing the volume in said one chamber (5).

17. (Currently amended) Hydraulic system according to claim 15 ~~or 16,~~ ~~characterized in that,~~ wherein the arrangement comprises a third conduit (20) connected, via a valve (16), to the hydraulic liquid tank (19) which is connected to the conduit circuit (11) on the opposite side of the first conduit's (22) connection thereto relative to the second conduit (21), and ~~that~~ the valve (17) in the second conduit (21) is controllable to be closed and the valve (16) in the third conduit (20) is controllable to be open simultaneously when the piston is displaced in the direction for reducing the volume in said one chamber (5).

18. (New) Hydraulic system according to claim 2, wherein the pump (12) is arranged to control the flow rate of the hydraulic liquid in said circuit (11) and thereby control the effective rate of the hydraulic drive means (1).

19. (New) Hydraulic system according to claim 7, wherein it comprises means to store regenerated energy.

20. (New) Hydraulic system according to claim 16, wherein the arrangement comprises a third conduit (20) connected, via a valve (16), to the hydraulic liquid tank (19) which is connected to the conduit circuit (11) on the opposite side of the first conduit's (22) connection thereto relative to the second conduit (21), and the valve (17) in the second conduit (21) is controllable to be closed and the valve (16) in the third conduit (20) is controllable to be open simultaneously when the piston is displaced in the direction for reducing the volume in said one chamber (5).